



VARIABLE MESSAGE BOARD

PCMS BOARD

PLACE 1 PCMS BOARD S/B PRIOR TO ROYAL PALM WAY

1 PCMS BOARD S/B PRIOR TO GULFSTREAM DIRECTING TRUCK TRAFFIC TO USE S OCEAN BLVD

ENVIRONMENTAL LAND WILL FOLLOW FDOT STANDARD PLAN INDEX 102-600 SERIES & MUTCD



This Certifies that
Shawn A. Musgrave
Has Completed a Florida Department of Transportation
Approved Maintenance of Traffic (MOT) Advanced Course.

Date Expires 09/24/2019 Certificate # 11085
Instructor Catherine Witt FDOT Provider # 37

ATSSA
Phone: 540-368-1701
15 Riverside Parkway Ste. 100
Fredericksburg, FL
www.atssa.com
donna.clark@atssa.com



SAFER ROADS SAVE LIVES

DISTANCE BETWEEN SIGNS			
Speed	Spacing (ft.)		
	A	B	C
40 mph or less	200	200	200
45 mph	350	350	350
50 mph	500	500	500
*55 mph or greater	2640	1640	1000

THIS MAINTENANCE OF TRAFFIC ("MOT PLAN") IS THE EXCLUSIVE PROPERTY OF ACME BARRICADES, LLC, AND IS PROVIDED SOLELY FOR INFORMATIONAL AND PLANNING PURPOSES. THE MOT PLAN HAS BEEN DESIGNED FOR THE EXCLUSIVE AUTHORIZED INTERPRETATION AND IMPLEMENTATION BY ACME BARRICADES, LLC. THE MOT PLAN HAS NOT BEEN DESIGNED FOR DISTRIBUTION TO OR INTERPRETATION, IMPLEMENTATION AND RELIANCE BY ANY OTHER PARTY. ACME BARRICADES, LLC DOES NOT MAKE ANY WARRANTIES OR REPRESENTATIONS RELATED TO THIS MOT PLAN. CUSTOMERS SHALL SUBMIT THIS PLAN TO THE APPROPRIATE GOVERNING AUTHORITY FOR APPROVAL PRIOR TO IMPLEMENTATION BY ACME BARRICADES, LLC ONLY, PURSUANT TO AGREED UPON IMPLEMENTATION TERMS.

Table 1 Device Spacing				
Speed (mph)	Max. Distance Between Devices (ft.)			
	Cones or Tubular Markers		Type I or Type II Barricades or Vertical Panels or Drums	
	Taper	Tangent	Taper	Tangent
25	25	50	25	50
30 to 45	25	50	30	50
50 to 70	25	50	50	100