



In the control of the

te Residence Ionterey Road Im Beach

<u>L</u>

✓HEET L11.0

COPYRIGHT:

The following drawings are instruments of service to the Landscape Architect. They are not products of design. All ideas, designs, arrangements and plans indicated or represented by this/these drawings are owned by and the property of the designer and were created, evolved and developed for use on and in connection with this project. None of such ideas, designs, arrangements or plans shall be used by or disclosed to any person, firm or

DISCLAIMER:

Construction, as the term is generally understood, and that ENVIRONMENT DESIGN GROUP does not provide landscape architectural services during construction, including on—site monitoring, site visits, shop drawing review, design clarification, etc., the client agrees to indemnify and hold harmless ENVIRONMENT DESIGN GROUP from any liability arising from, acts or omissions in the performance of said services during construction by the client, and his/her agents, employees, or subcontractors.

48 HOURS BEFORE DIGGING

CALL TOLL FREE

1-800-432-4770

SUNSHINE STATE ONE CALL
OF FLORIDA, INC.

COA-22-028
ZON-22-079
Rendered Landscape Elevations
SCALE IN FEET O' 4' 8' 12'





COPYRIGHT:

The following drawings are instruments of service to the Landscape Architect. They are not products of design. All ideas, designs, arrangements and plans indicated or represented by this/these drawings are owned by and the property of the designer, and were created, evolved and developed for use on and in connection with this project. None of such ideas, designs, arrangements or plans shall be used by or disclosed to any person, firm or corporation without the written permission of the Landscape Architect.


48 HOURS BEFORE DIGGING CALL TOLL FREE 1-800-432-4770

COA-22-028 ZON-22-079 Rendered Landscape Elevations

DE/IG/I GROUP Landscape Architecture Land Planning Landscape Management Dustin M. Mizell, MLA RLA #6666784 Dustin@environmentdesigngroup.com

JOB NUMBER: # 22070.00 LA
DRAWN BY: Sean Twomey
DATE: 05.13.2022


✓HEET L11.1




48 HOURS BEFORE DIGGING CALL 1-800-432-4770 SUNSHINE STATE ONE CALL OF FLORIDA, INC. Contractor is responsible for obtaining location of existing utilities prior to commencement of construction activities.

Via Marila

Location Map N.T.S.





Renovation

pe

Legend


EXISTING ELEVATION PER WALLACE SURVEYING CORP. (NAVD-88)


PROPOSED ELEVATION (NAVD-88)

FLOW DIRECTION

EXFILTRATION TRENCH AREA DRAIN

24" NYLOPLAST DRAIN BASIN WITH BAFFLE





Chad M. Gruber FL P.E. No. 57466

Plan Background from Hardscape Plan by Environment Design Group Received 3/25/22 ARC-22-___

© 2022 Gruber Consulting Engineers, Inc.

Sheet No. **C-**1



A. SITE INFORMATION

Total Property Area = 8,462 sq.ft.

Drainage Area Impervious Surface (existing residence, proposed driveway, deck, walkway, pool) = 4,189sq.ft.

Drainage Area Pervious Surface = 4,273 sq.ft.

B. ESTIMATED STORMWATER RETENTION VOLUME

The retention volume is estimated using the Rational Method (Q=CiA)

C = 1.0 (impervious surface)

C = 0.2 (pervious surface) i = 2 in/hr

Impervious Surface Runoff Volume:

 $1.0 \times 2 \text{ in/hr} \times 4,189 \text{ sq.ft.} \times 1 \text{ ft./12 in.} = 698 \text{ cu.ft.}$

Pervious Runoff Volume: $0.2 \times 2 \text{ in/hr} \times 4,273 \text{ sq.ft.} \times 1 \text{ ft./}12 \text{ in.} = 142 \text{ cu.ft.}$

Total Volume to be Retained = 840 cu.ft.

C. PROPOSED EXFILTRATION TRENCH SIZING

Total Length of Trench Provided = 45 ft Trench Width

= 0.00005 cfs/sq.ft./ft. of head Hydraulic Conductivity Depth to Water Table = 4.00 ft

DU = Un-Saturated Trench Depth = 2.50 ft

DS = Saturated Trench Depth = 0.00 ft

V = Volume Treated = 1,007 cu.ft.

Notes:

- 1) Exfiltration trenches and storm piping to be protected from roots with a root barrier.
- 2) Roof drain downspouts are to be connected to the proposed drainage system. Contractor to provide engineer with downspout locations prior to installation of drainage system.
- 3) Exfiltration trench design uses an assumed value of hydraulic conductivity. Client may obtain a site specific test for hydraulic conductivity prior to exfiltration trench installation.
- 4) Contractor shall mill and overlay all roadway cuts a minimum of 50 ft. on either side of the excavation the entire width of each affected lane.
- 5) Contractor is responsible for installing and maintaining erosion control measures during construction.
- 6) Video inspection of storm drainage system required prior to installation of sod.