

Printed copies of this document are not considered signed and sealed and

the SHA authentication code must be verified on any electronic copies.

© 2024 Gruber Consulting Engineers, Inc.

## March 2025

# Landscape set

# NAEGELE RESIDENCE COA-24-0025 ZON-24-0065

Residential 70 Middle Rd, Palm Beach, FL 33480

DRAWING IN	NDEX
Sheet No.	Sheet Title
L-101	EXISTING CONDITION PHOTOS
L-101.1	EXISTING CONDITION PHOTOS
N/A	PREVIOUSLY APPROVED LANDSCAPE PLAN (ENCLOSED
L-102	PROPOSED LANDSCAPE PLAN
L-103	LANDSCAPE PLAN (RENDERING)
L-104	LANDSCAPE DETAILS AND NOTES
L-105	PLANT MATERIAL
L-106	NATIVE AND NON-NATIVE PLAN
L-107	FRONT YARD OPEN SPACE
L-108	PERIMETER OPEN SPACE
L-109	OPEN SPACE DIAGRAM
CE-1	COLORED ELEVATION
CE-2	COLORED ELEVATION
CE-3	COLORED ELEVATION
CE-4	COLORED ELEVATION
CE-5	COLORED SITE PLAN



NAEGELE RESIDENCE
70 Middle Rd
Polm Reach El 33480

SHEET TITLE

Cover sheet

03/03/2025

Mar 2025

DRAWN


SCALE

Theres Digitally signed by Theresa Wymer Date:

Wymer 2025.02.25
21:30:49 -05'00'

THERESA WYMER LA6667363

SHEET NUMBER




SUBJECT PROPERTY: EAST ELEVATION (front)



**SOUTH ELEVATION (side)** 



SOUTH ELEVATION (side)



**SOUTH ELEVATION (side)** 

PARAMETRIKA LAND & DESIGN Gabriela Albornoz Theresa Wymer LA6667363



AEGELE RESIDENCE
70 Middle Rd

existing conditions

REVISION

Mar 2025

03/03/2025

design **GA** 

DRAWN **TY** 

SCALE **N/A** 

Theres Digitally signed by Theresa Wymer Date:
2025.02.25
21:31:16 -05'00'

THERESA WYMER LA6667363

SHEET NUMBER
L-101





**Existing conditions** 

Mar 2025

03/03/2025

Theresa Digitally signed by Theresa Wymer

Oate:
2025.02.25
21:31:31-05'00' THERESA WYMER LA6667363


SHEET NUMBER








INTERIOR COURTYARD













LARGE PALM / PLANTING DETAIL




MULTI-TRUNK AND SMALL TREE (2' cal. and under)



DO NOT CUT LEADER PRUNE DAMAGED OR DEAD WOOD INMEDIATELT PRIOR TO PLANTING AS DIRECTED BY THE LANDSCAPE ARCHITECT - PROTECT TREE WITH BURLAP 1" WIDE MIN. NYLON STRAPING AT EQUAL SPACING (3 PER TREE) -- MULCH, 1" DEEP ON ROOT ZONE → 3" BASIN FOR WATERING — MULCH, 3" DEEP 1/2" x 2' FLOURESCENT ORANGE MARKER SET CROWN OF ROOT BALL 0' — 2" ABOVE SURROUNDING FINISH GRADE, UNTIE BURLAP FROM BASE OF TRUNK. TRIM AS NECESSARY 2"x 2"x 2' STAKE TOP TO BE 2" MIN BELOW FINISH GRADE BACKFILL WITH PLANTING SOIL ON UNDISTURBED SOIL

cal. and over) LARGE TREE / PLANTING DETAIL



LAN[	DSCAPE NOTES
	Non Cypress variety
2	All plants shall mee

y mulch shall extend under all trees, shrubs and ground cover beds to the closest hard edge or sod border, in a minimum of 3" depth, eet the minimum standard of Florida No. 1 or better as specified in Grade and Standards for Nursery Plants as published by the Division of Plant Industry, Florida Department of Agriculture, latest edition.

All shrubs to be planted a minimum of 24", and ground covers a minimum of 12" from the edge of walks, building walls, pond's edge, etc... Ixora Nora and Raphiolepsisi Indica to be planted 30" form edge of walkways.

All tees and palms over 8" in height shall be braced to prevent lateral movement for a period of six months from the date of planting, Either wood braces shown in the planting detail, or the wire and furnbuckle method shall be used. No nails, screws, metal straps or wires are to be used directly against the trees or

All palms except for species sush as Cocos, Acoelorraphe. Raphis, and other multitrunk palms, shall have straight trunks, free of scars, decay or anu

caused by digging, transport or planting handling of the same, 6. All work by the Landscape Contractor shall be performed in a professional and sound manner in accordance with established standards of landscape installation practices and workmanship.

Landscape Contractor is responsible for verifying plant quantifies prior to bidding. Quantifies shown in the plans may vary due to actual site scale, job conditions, etc... Landscape Architect assumes no responsability for the actual plant count necessary for the successful completion of the work. 8. Landscape Contractor and his subcontractors shall be licensed and insured as requierd by the municipality, country, state or any toher governmental agency requiring a license or insurance in order for the Landscape Contractor to perform his work. All work shall comform to Miami-Dade County's landscape ordinance Chapter 18-A. ordinance

98-13, and any other municipal landscape ordinance in effect at the projects location, includins streets-tres.


BARRICADE FENCING DETAIL

Landscape Contractor is requierd to procure and obtain any necessary permits aplicable for the sucesful completion of this project, if applicable. Landscape material shall not be allowed to grow in such a manner as to impede streetfront triangle of visibility to property owner or neighboors, so as to materially impede vission between a height of 3 feet and 8 feet.

Landscape Contractor shall call Sunshine State One Call Center of Florida at 1-800-432-4770 (Toll Free) 48 hours before digging. Landscape Contractor is responsible for inspectinh the site and phisically observing all the site conditions proir to entering into Agreements or Contract with Owner. Landscape Contractor shall coordinate his work with the General Contractor of Construction Manager in such a manner as to allowed for a speedy and orderly completion of all work on the site.

Any excess soil, landscape materials and debris from the landscape Contractor's work shall be removed from the site inmediately upon completion of his

Landscape Contractor shall coordinate the proposed planting in the Planting Plan with the work requierd in recolacting and removal of trees in sheet L-L (Existing Trees). 16. One year warranty



Line#	Landscape Legend			
1	Property Address:	70 Middle Rd, Palm Beach, FL 33480		
2	Lot Area (sq. ft.):	15,495 sq. ft.		
3		REQUIRED	PROPOSED	
4	Landscape Open Space (LOS) (Sq Ft and %)	6,973 sq. ft. / 45% MIN.	5,510 sq. ft. / 35.6%	
5	LOS to be altered (Sq FT and %)	N/A		
6	Perimeter LOS (Sq Ft and %)	1,816-sq, ft. / 50%	2,238 sq. ft. / 61%	
7	Front Yard LOS (Sq Ft and %)	1,695 sq. ft. / 40%	1,757 sq. ft. / 51%	
8	Native Trees %	30% (number of trees)	33.3 % (1)	
ĝ	Native Shrubs & Vines %	30% (number of shrubs & vines)	50%	
10	Native Groundcover %	30% (groundcover area)	100%	

the Institute for Regional Conservation Natives for Your Neighborhood FL Statewide Plant List

the Florida Native Plant Society Native Plants for Your Area List Note: Modification of >50% of existing landscape/greenscape are subject to minimum native plant requirements and must submit a landscape and irrigation plan for review.

This table shall be included on the landscape species index sheet as prepared by a licensed landscape architect and landscape openspace data shall be incorporated on to corresponding zoning legend. REV BF 20230727 See Ord. 003-2023

PARAMETRIKA LAND & DESIGN Gabriela Albornoz Theresa Wymer LA6667363



**RESIDEN** ш

Landscape details and notes

ISSUE DATE 03/03/2025

REVISION

Mar 2025

DESIGN

N/A

Theresa by Theresa Wymer Wymer 2025.02.25 21:32:34 -05'00


SHEET NUMBER

THERESA WYMER

LA6667363








SHEET TITLE

Plant material

ISSUE DATE 03/03/2025

REVISION
Mar 2025



SHEET NUMBER L-105





SAL

Sataketia liukiuensis




COE Conocarpus erectus





COES Conocarpus erectus 'sericeus'




ERL Ernodea littoralis Sw.











SHEET NUMBER CE-1



**EAST ELEVATION** 



**EAST ELEVATION WITH SITE WALL** 



EAST ELEVATION WITH SITE WALL & HEDGES



**WEST ELEVATION** 

SHEET TITLE
COLORED ELEVATION

ISSUE DATE 03/03/2025

REVISION Mar 2025

DESIGN GA

DRAWN **TY** 

> SCALE N/A

Theresa Digitally signed by Theresa Wymer Date:
2025.02,25
21:34:54 -05'00'

SHEET NUMBER

Theresa Wymer La666*7*363





NORTH ELEVATION SHOWN WITHOUT FOUNTAIN & PLANTERS

NORTH ELEVATION SHOWN WITH FOUNTAIN & PLANTERS





NORTH FOUNTAIN & SITE WALL ELEVATION

SOUTH ELEVATION WITH SITE WALL

THERESA WYMER LA6667363

> SHEET NUMBER CE-3



SOUTH SECTION THROUGH COURTYARD SHOWING PALM TREES AROUND POOL



SOUTH SECTION THROUGH COURTYARD SHOWING TABEBUIA TREE



**SOUTH ELEVATION VIEW** FROM THE STREET



SOUTH SECTION THROUGH COURTYARD FACING SOUTH

EAST SECTION THROUGH COURTYARD FACING EAST



WEST SECTION THROUGH COURTYARD FACING WEST



EAST ELEVATION FACING EAST FROM FRONT DOOR

PARAMETRIKA LAND & DESIGN
Gabriela Albornoz



NAEGELE RESIDENCE

SHEET TITLE

COLORED ELEVATION

03/03/2025

REVISION

Mar 2025

DESIGN **GA** 

DRAWN **TY** 

SCALE N/A

Theresa Digitally signed by Theresa Wymer
Wymer Date:
2025.02.25
21:35:35 -05'00'

THERESA WYMER
LA6667363

SHEET NUMBER

SITE AND LANDSCAPE PLAN

SANCENCE STANCES CONTRACTOR STANCES



# NAEGELE RESIDENCE


COLORED ELEVATION

03/03/2025

Dec 2024

Theresa by Theresa Wymer Wymer Date: 2025.02.25 21:35:55 -05'00 THERESA WYMER LA6667363

> SHEET NUMBER CE-5



# 70 Middle Road: 6 Variances

REVISED 1/29/25

### Please note: 2024 Variances: The 6 current Variances reference 3 specific areas with 3 New Variances.

The 3 specific areas show the number of Variances required. Please review the "Variance Synopsis" detailed below:

- 1) a) Construction of a previously approved **7 foot covered terrace** on existing 1969 non-original 1-story flat roof.
- b) In addition, the Owner needs to INSTALL new OSHA recommended flush Roof steps to safely access the 2 flat roofs. The OSHA recommended steps are a necessity and not a frivolity. The OSHA recommended steps are a safety measure so the owner's staff and maintenance crew do not suffer catastrophic FALLS, INJURY or DEATH while performing various maintenance and/ or roof repairs. The approval of the OSHA recommended steps will not confer any special privilege nor would they be detrimental to the public welfare. However, not installing the OSHA recommended steps could result in injury or death; of which the owner is seeking to avoid 3rd party liability. (not visible from any angle, any street view or any right of way)(whereby a NEW variance was added).


(3 Variances: Variance # 2,3,4)

- 2) Construction of a previously approved **8-foot laundry room addition** (91 sq. ft.) to the existing 1952 non-original structure.
- (3 Variances: Variance # 1,2,3)
- 3) Construction of a previously approved **South equipment enclosure** to enclose the pool, future fountain and A/C equipment. Installation of fountain equipment located 54.5 feet away from the water's edge.
- (2 Variances: Variance # 5,6)

### Variances: 70 Middle Road


- 1. Section 134-893(b)(11): A variance to increase lot coverage for a previously approved 8 foot laundry room addition resulting in lot coverage of 34.47% in lieu of the 33.07% existing and 30% maximum allowed under the Code.
- 2. Section 134-893(b)(13): A variance to increase the cubic content ratio ("CCR") for the previously approved laundry room addition and previously approved covered terrace resulting in a Cubic Content Ratio of 8.59 in lieu of the 8.44 existing and the 3.95 maximum allowed under the Code.
- 3. Section 134-893(b)(7): A variance to reduce the side (North) yard setback for the previously approved laundry room addition and previously approved terrace railing addition (on an existing 1-story flat roof) resulting in a North side yard setback of 7.6 feet in lieu of the 12.5 foot minimum required under the Code.
- 4. Section 134-893(b)(10): A variance to increase building height of 27.4 feet in lieu of the 22 feet required under the Code for the previously approved 7-foot covered terrace (on the existing 1-story flat roof). Increase of overall building height for the OSHA recommended Rooftop steps resulting in 47.1 feet in lieu of the 30 feet required under the Code (13 inches higher than the existing 46 feet high flat roof).
- 5. Section 134-1728(c)(5): A variance to reduce the street (South) side yard setback for existing pool equipment and fountain equipment resulting in a street side yard setback of 15.6 feet in lieu of the 20 foot minimum required under the Code. Increase the distance between the fountain's water's edge and the fountain equipment located 54.5 feet away from the water's edge in lieu of the 25 feet maximum allowed under the Code.
- 6. Section 134-1667(a): A variance to increase the height of the previously approved South equipment enclosure walls in the street (South) side yard setback to 6.9 feet in height in lieu of the 6 foot maximum allowed under the Code.


- a) Please Note: The previous Attorney forgot to include the height variance required for the previously approved "addition of a 7-foot covered terrace on the 1962 non-original existing 1-story flat roof". To <u>avoid</u> INJURY or DEATH (and to avoid 3<sup>rd</sup> party liability) the Owner needs to INSTALL new OSHA recommended Rooftop steps to safely access the 2 flat roofs ( not visible from any angle, street view or right of way)(whereby a NEW variance was added ).
- b) In 2019, the owner did not know that the "pool equipment" would need to be relocated ( whereby a NEW variance was added). The pool can <u>not</u> be installed until it is known where the pool equipment will be located due to running pipe and conduits etc.).
- c) The owner is proposing a "front yard fountain" (using the original fountain set within a half circle fountain (whereby a NEW variance is required to allow for the future fountain equipment to be enclosed within the previously approved South equipment enclosure); of which will also provide the required solid wall screening concealing and providing a sound barrier for pool, fountain and A/C units in the South equipment enclosure.
- d) The previously approved South equipment enclosure requires a "height variance" to cover and screen the pool equipment, fountain equipment and the A/C Units (whereby a NEW variance was added); of which will also provide the required solid wall screening concealing and providing a sound barrier for equipment located in the South equipment enclosure.
- e) Re: The previously approved "8 foot laundry room addition (91 sq. ft.) to the existing 1952 non-original structure": **The 8 foot** Laundry room addition will provide the required solid wall screening concealing and providing a sound barrier for the existing A/C equipment in the North A/C equipment enclosure.
- f) These Variances will allow the Owner to finish 3 major areas to include:
  - b1) Family Room Rebuild (North side of House)
  - b2) Laundry Room Rebuild (North west corner of house)
  - b3) Pool installation



### NOTES FROM THE OWNER:

- THE OSHA APPROVED STEPS ARE A SAFETY MEASURE SO THE OWNERS STAFF AND MAINTENANCE CREW DO NOT SUFFER CATASTROPHIC FALLS FROM THE ROOF WHILE PERFORMING VARIOUS MAINTENANCE AND/OR ROOF REPAIRS.
- THE OSHA APPROVED STEPS ARE A NECESSITY.
- THE OWNER'S FLAT ROOFS REQUIRE RE-PAINTING AND WATERPROOFING SEMI-ANNUALLY.
- 4) THE OWNER'S 3 CHIMNEYS FREQUENTLY REQUIRE CLEANIN AND MAINTENANCE DUE TO EXCESSIVE LEAVES AND DEBRIS WHICH OFTEN ACCUMULATE ON THE FLAT ROOFS DURING HIGHWINDS, STORMS AND HURRICANES.
- 5) THE OWNER'S HAND MADE CLAY ROOF TILES OFTEN CRACK BREAK AND DETACH DURING HIGH WINDS, STORMS AND HURRICANES; WHICH REQUIRE IMMEDIATE REPLACEMENT TO AVOID FUTURE CODE VIOLATIONS.
- 6) THE OSHA APPROVED STEPS PROVIDE A SAFER AND MORE EFFICIENT ACCESS BETWEEN THE TWO FLAT ROOFS; REDUCING THE NEED FOR LADDERS AND OTHER POTENTIALLY HAZARDOUS ACCESS METHODS TO TRANSITION BETWEEN THE TWO FLAT ROOF FOR CHIMNEY AND ROOF ACCESS.
- 7) THE OSHA APPROVED STEPS ARE NOT VISIBLE FROM ANY RIGHT OF WAY OR STREET VIEWS.
- 8) APPROVAL OF THE OSHA APPROVED STEPS WILL NOT CONFER ANY SPECIAL PRIVILEGE NOR WOULD THEY BE DETRIMENTAL TO THE PUBLIC WELFARE. HOWEVER, NOT INSTALLING THE OSHA APPROVED STEPS COULD RESULT IN INJURY OR DEATH; OF WHICH THE OWNER IS SEEKING TO AVOID 3RD PARTY LIABILITY.





### ROOF STRINGER STEPS NOT VISIBLE FROM STREET OR RIGHT OF WAY



70 Middle Road



MIDDLE RD - EAST VIEW



MIDDLE RD - NORTH VIEW



MIDDLE RD/VIA MARINA CORNER



VIA MARINA - SOUTH VIEW



PHOTOS SHOWING ROOF STEPS NOT VISIBLE FROM STREET OR RIGHT OF WAY





### EXISTING NORTH ELEVATION

SCALE: 37"=1'-0"





SCALE: 32"=1'-0"





### EXISTING WEST ELEVATION






### PREVIOUSLY APPROVED WEST ELEVATION


SCALE: 32"=1'-0"









- 1. Section 134-893(b)(11): A variance to increase lot coverage for previously approved 8 foot laundry room addition resulting in lot coverage of 34.47% in lieu of the 33.07% existing and 30% maximum allowed under the Code.
- 2. Section 134-893(b)(13): A variance to increase the cubic content ratio ("CCR") for the previously approved laundry room addition and covered terrace resulting in a Cubic Content Ratio of 8.59 in lieu of the 8.44 existing and the 3.95 maximum allowed under the Code.
- 3. Section 134-893(b)(7): A variance to reduce the side (North) yard setback for the previously approved laundry room addition and previously approved terrace railing addition (on an existing 1-story flat roof) resulting in a North side yard setback of 7.6 feet in lieu of the 12.5 foot minimum required under the Code.




- 2. Section 134-893(b)(13): A variance to increase the cubic content ratio ("CCR") for the previously approved laundry room addition and previously approved covered terrace resulting in a Cubic Content Ratio of 8.59 in lieu of the 8.44 existing and the 3.95 maximum allowed under the Code.
- 3. Section 134-893(b)(7): A variance to reduce the side (North) yard setback for the previously approved laundry room addition and previously approved terrace railing addition (on an existing 1-story flat roof) resulting in a North side yard setback of 7.6 feet in lieu of the 12.5 foot minimum required under the Code.
- 4. Section 134-893(b)(10): A variance to increase building height of 27.4 feet in lieu of the 22 feet required under the Code for the previously approved 7-foot covered terrace (on the existing 1-story flat roof). Increase of overall building height for the OSHA recommended Rooftop steps resulting in 47.1 feet in lieu of the 30 feet required under the Code (13 inches higher than the existing 46 feet high flat roof).





5. Section 134-1728(c)(5): A variance to reduce the street (South) side yard setback of previously approved South equipment enclosure for existing pool equipment and fountain equipment resulting in a street side yard setback of 15.6 feet in lieu of the 20 foot minimum required under the Code. Increase the distance between the fountain's water's edge and the fountain equipment located 54.5 feet away from the water's edge in lieu of the 25 feet maximum allowed under the Code.



6. Section 134-1667(a): A variance to increase the height of the previously approved South equipment enclosure walls in the street (South) side yard setback to 6.9 feet in height in lieu of the 6 foot maximum allowed under the Code.

- 1. The special conditions and circumstances related to the subject property is that this is a Historic Landmarked house in the R-B Zoning District that is currently non-conforming to the current Code.
- 2. The special conditions and circumstances are not the result of the applicant as the house was built in 1924 (with later additions in 1952 and 1969). The non-conforming aspects of the house were in existence at the time of acquisition by the applicant.
- 3. The hardship, which runs with the land, is that the house is a Town of Palm Beach Historic Landmark house (built in 1924) which is non-conforming in several aspects to the current Code as zoning has changed since the house was originally constructed 100 years ago.
- 4. The current location and configuration of the Landmark house limits the applicant's ability to make changes without the necessity for variances. Renovations to a Landmark house require a delicate approach in making changes to improve the livability for the year 2024.
- 5. The previously approved 8-foot laundry room addition (extended from the 1952 non-original structure) is relatively small and will allow for greater livability of the property to conform to current standards. The variances requested are the minimum necessary to make reasonable use of the land. The previously approved 8-foot (91 square foot) laundry room addition in the North West corner of the house will be no farther into the setback than the rest of the house currently is. The previously approved 8-foot laundry room addition will be no closer to the North property line than other portions of the house currently are (to also include providing the required solid wall screening concealing and providing a sound barrier for the existing North A/C equipment).

- 6. The previously approved 7-foot covered terrace on the existing 1-story flat roof of the 1969 non-original addition will not be any closer to the North property line than the flat roof currently is; nor would it be any higher than the original clay barrel tile roof currently is. The previously approved 7-foot covered terrace is a significant improvement to the 1969 non-original 1-story addition creating cohesion and unification of the North exterior elevation of the Landmarked house.
- 7. The relocation of the pool equipment and future fountain equipment are necessary for the pool, spa and fountain and will be enclosed within the previously approved South equipment enclosure. The pool equipment and fountain equipment will be lower in height and farther from the property line than the existing equipment is currently situated (concealed within the South equipment enclosure providing the required solid wall screening and sound barriers).
- 8. The OSHA recommended steps are a safety measure so the owner's staff and maintenance crew do not suffer catastrophic FALLS, INJURY or DEATH while performing various maintenance and/ or roof repairs. The owner's flat roofs require re-painting and waterproofing semi-annually. The owner's 3 chimneys frequently require cleaning and maintenance due to excessive leaves and debris which often accumulate on the flat roofs during high winds, storms and hurricanes. The owner's hand made clay roof tiles often crack, break and detach during high winds, storms and hurricanes; which require immediate replacement to avoid future code violations. The OSHA recommended steps provide a safer and more efficient access between the two flat roofs; reducing the need for ladders and other potentially hazardous access methods to transition between the two flat roofs for chimney and roof access. The OSHA recommended steps are not visible from any right of way or street views. The OSHA recommended steps are a necessity and not a frivolity. The approval of the OSHA recommended steps will not confer any special privilege nor would they be detrimental to the public welfare. However, not installing the OSHA recommended steps could result in injury or death; of which the owner is seeking to avoid 3rd party liability.
- 9. The granting of these variances will not be injurious to the area involved or detrimental to the public welfare. Granting of the variances requested will not confer any special privilege that is denied to the neighboring properties.